

Company Name Address:

Pro-Link, Inc. 500 Chapman St. Canton, MA 02021

Information Telephone Number(s)

781-828-9550

Section 1 - Product InformationProduct Name (ID #): **XLink Mix Finish**~~(5276)~~

EMERGENCY TELEPHONE NUMBER

Product Type: **Wood Floor Coating**

1-800-535-5053

Section 2 - Information on Ingredients

Chemical Name	% by Weight	Cas #	OSHA PEL	ACGIH TLV
*Dibutyl Phthalate (RQ)	< 5%	84-74-2	5 mg/m3	5 mg/m3
*Diethylene Glycol Methyl ether	< 10%	111-77-3	NE	NE

83

*Chemicals marked with an asterick in Section Two are subject to the reporting requirements for Section 313 of Title III of the Superfund Amendments & Reauthorization Act (SARA) of 1986 & 40 CFR Part 372.

Section 3 - Hazards Identification**Emergency Overview:**

Keep Out of Reach of Children. CAUTION: May cause eye irritation. Prolonged contact with skin may cause irritation. May cause gastro intestinal irritation if swallowed.

Potential Health Effects**Primary Routes of Exposures**

Eyes, skin and oral are the principle routes of exposure

Acute Eye Contact:

May cause burning sensation and eye irritation.

Acute Skin Contact:

Prolonged and repeated skin contact may cause skin irritation.

Acute Ingestion:

May cause gastro intestinal irritation if swallowed.

Acute Inhalation:

NA

Chronic Information:

Unknown

Carcinogenicity: IARC - No

NTP - No

OSHA - No

ACGIH - No

Section 4 - First Aid Measures**Skin Contact:**

Flush with plenty of water for 15 minutes. Remove contaminated clothing. Wash before reuse. If irritation persists, call physician.

Eye Contact:

Immediately flush eyes with plenty of water for 5 - 10 minutes. Get medical attention, if irritation persists.

Ingestion:

If swallowed, give quantities of water to dilute stomach contents. Induce vomiting only as directed by medical personnel. Get medical attention immediately.

Inhalation:

NA

(If any condition persists - Consult a physician).

Section 5 - Fire Fighting Measures

Flash Point (Method): None

Flammable Limits: LFL NA

UFL: NA

Fire & Explosion Hazards: NA

Extinguishing Media:

NA

Special Fire Fighting Procedures:

NA

Hazardous Combustion Products:

None

Section 6 - Accidental Release Measures

Contain spill. Mop up, rinse with water.

Section 7 - Handling and Storage

Store so as to be inaccessible to children. Keep from freezing. Wash thoroughly after handling.

Section 8 - Exposure Controls Personal Protection**Eye Protection:**

Safety Glasses

Skin Protection:

Rubber gloves, if prolonged contact

Respiratory Protection:

None normally required if ventilation is adequate.

Ventilation Requirements:

Normal ventilation should be adequate.

Other:

Chemical apron when handling large volumes of material.

Section 9 - Physical / Chemical Properties

Physical Form:	Liquid	pH:	8.5 ± 0.5
Color:	Off white, opaque	Specific Gravity:	1.032
Odor:	Slight amine	Solubility:	Dispersible
Boiling Point:	Approximately 212°F	Freezing Point:	NE
Evaporation Rate:	About the same as water.	% Volatile:	75%
Vapor Pressure:	NE	V.O.C.	86gm/l

Section 10 - Stability and Reactivity**Stability:**

This product is stable at ambient temperature and pressure.

Hazardous Decomposition Products:

None

Hazardous Polymerization:

Will not occur

Incompatibility:

None